

# TIRE PREP

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product identifier**

|               |           |
|---------------|-----------|
| Chemical Name | Mixture   |
| CAS No.       | Mixture   |
| Trade Name    | TIRE PREP |
| Product Code  | EN-5394   |

**Relevant identified uses of the substance or mixture and uses advised against**

|                      |         |
|----------------------|---------|
| Identified Use(s)    | CLEANER |
| Uses Advised Against | None    |

|                        |  |
|------------------------|--|
| Company Identification | Spray Products Corporation<br>P.O. Box 737<br>Norristown, PA 19404 |
|------------------------|--|

|                           |  |
|---------------------------|--|
| Telephone                 | (610) 277-1010   |
| Fax                       | (610) 277-4390   |
| E-Mail (competent person) | <a href="mailto:sds@sprayproducts.com">sds@sprayproducts.com</a> |

**Emergency telephone number**

|                     |   |
|---------------------|---|
| Emergency Phone No. | <b>Transportation Emergency:</b> CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted) |
|---------------------|---|

### SECTION 2: HAZARDS IDENTIFICATION

**Classification of the substance or mixture**

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Compressed dissolved gas; STOT SE 3; Skin Irrit. 2; Eye Irrit. 2; Asp. Tox. 1

**Label elements**

Hazard Symbol



**DANGER**

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May cause drowsiness or dizziness.  
May cause respiratory irritation.  
Causes skin irritation. Causes serious eye irritation.  
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Use only outdoors or in a well-ventilated area.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Do not breathe mist/vapours/spray.  
Wash hands and exposed skin after use.  
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.  
Keep out of reach of children.

# TIRE PREP

## Other hazards

Harmful to aquatic life.

## Additional Information

Contains: residual Toluene (CAS No. 108-88-3) ~ ≤ 0.13%. Studies in animals have shown that repeated exposures to toluene produce adverse reproductive effects. However, in similar animal studies, mixed xylenes containing up to 2.4% residual toluene did not result in reproductive or developmental toxicity. As such, this product has not been classified as a reproductive toxicant.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredient(s)              | % wt. * | CAS No.     | Hazard classification   |
|--------------------------------------|---------|-------------|---|
| Acetone                              | 45 - 55 | 67-64-1     | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336   |
| Xylene                               | 20 - 25 | 1330-20-7   | Flam. Liq. 3; H226<br>Eye Irrit. 2; H320<br>Skin Irrit. 2; H315<br>Asp. Tox. 1; H304<br>STOT SE 3; H335                               |
| Heptane, branched, cyclic and linear | 15 - 25 | 426260-76-6 | Flam. Liq. 2; H225<br>Asp. Tox. 1; H304<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Aquatic Acute 2; H401<br>Aquatic Chronic 3; H412 |
| Carbon dioxide                       | 7-15    | 124-38-9    | Compressed dissolved gas  |

**Additional Information** - Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.:

- Ethylbenzene (CAS No. 100-41-4) ~ ≤ 5%
- Toluene (CAS No. 108-88-3) ~ ≤ 0.13%

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. Seek medical treatment.

### Most important symptoms and effects, both acute and delayed

Aspiration of droplets may cause pulmonary oedema. May cause drowsiness and dizziness.

### Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

# TIRE PREP

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

-Suitable Extinguishing Media  
-Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.  
Do not use water jet.

### Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

### Environmental precautions

Prevent liquid entering sewers, basements and work pits.

### Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

### Reference to other sections Additional Information

None  
None

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

### Conditions for safe storage, including any incompatibilities

-Storage temperature

Store locked up. Keep in a cool, well ventilated place. Protect from sunlight. Store at temperatures not exceeding 50 °C / 122 °F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

### Specific end use(s)

Automotive Care Product




## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

| SUBSTANCE.                           | CAS No.     | (8hr TWA)  |                        | (STEL)     |             | Note:            |
|--------------------------------------|-------------|------------|------------------------|------------|-------------|------------------|
|                                      |             | PEL (OSHA) | TLV (ACGIH)            | PEL (OSHA) | TLV (ACGIH) |                  |
| Acetone                              | 67-64-1     | 1000 ppm   | 500 ppm                | -----      | 750 ppm     | ^NIC             |
| Toluene                              | 108-88-3    | 200 ppm    | 20 ppm                 | 300 ppm*   | -----       | *10-min. Ceiling |
| Xylene                               | 1330-20-7   | 100 ppm    | 100 ppm                | -----      | 150 ppm     | -----            |
| Ethylbenzene                         | 100-41-4    | 100 ppm    | 20 ppm                 | -----      | -----       | -----            |
| Heptane, branched, cyclic and linear | 426260-76-6 | 500 ppm**  | 1500 mg/m <sup>3</sup> | -----      | -----       | **n-heptane      |
| Carbon dioxide                       | 124-38-9    | -----      | 5000 ppm               | -----      | 30,000 ppm  | -----            |

^NIC = Notice of Intended Changes (ACGIH®);

# TIRE PREP

|   |  |
|---|--|
| <b>Recommended monitoring method</b>  | NIOSH 1300 (Ketones I); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1501 (Hydrocarbons, Aromatic)                             |
| <b>Exposure controls</b>  |  |
| <b>Appropriate engineering controls</b>   | Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.   |
| <b>Personal protection equipment</b>  |  |
| Eye/face protection   | Wear protective eyewear (goggles, face shield, or safety glasses).   |
|  |  |
| Skin protection (Hand protection/ Other)  | Wear suitable gloves if prolonged skin contact is likely (Viton®/Butyl rubber). Check with protective equipment manufacturer's data. |
|  |  |
| Respiratory protection  | Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.  |
|  |  |
| Thermal hazards   | Not normally required. Use gloves with insulation for thermal protection, when needed.   |
| <b>Environmental Exposure Controls</b>  | None known   |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|  |                                  |
|--|----------------------------------|
| Appearance                               | Aerosol Spray                    |
| Color.                                   | Colorless                        |
| Odor                                     | Acetone-like                     |
| Odor Threshold (ppm)                     | Not available                    |
| pH (Value)                               | Not available                    |
| Melting Point (°C) / Freezing Point (°C) | Not available                    |
| Boiling point/boiling range (°C):        | 56 (Acetone)                     |
| Flash Point (°C)                         | -17 (Acetone)                    |
| Evaporation Rate                         | Not available                    |
| Flammability (solid, gas)                | Not applicable                   |
| Explosive Limit Ranges                   | 2.5% - 12.8% v/v (Acetone)       |
| Vapor pressure (Pascal)                  | $2.4 \times 10^4$ (Acetone)      |
| Vapor Density (Air=1)                    | Not available                    |
| Density (g/ml)                           | Not available                    |
| Solubility (Water)                       | Not available                    |
| Solubility (Other)                       | Not available                    |
| Partition Coefficient (n-Octanol/water)  | Not available                    |
| Auto Ignition Point (°C)                 | 465 (Acetone)                    |
| Decomposition Temperature (°C)           | Not available                    |
| Kinematic Viscosity @ 20 °C              | <0.9 mm <sup>2</sup> /s (Xylene) |
| Explosive properties                     | Not explosive.                   |
| Oxidizing properties                     | Not oxidizing.                   |
| <b>Other information</b>                 | <b>VOC:</b> 44%                  |

## SECTION 10: STABILITY AND REACTIVITY

|   |                                 |
|---|---------------------------------|
| <b>Reactivity</b>                         | Stable under normal conditions. |
| <b>Chemical stability</b>                 | Stable.                         |
| <b>Possibility of hazardous reactions</b> | None anticipated.               |

# TIRE PREP

**Conditions to avoid**

Avoid contact with heat and ignition sources.

**Incompatible materials**

Strong oxidizing agents. Reducing agents. Acids. Bases. Chlorinated compounds. Aldehydes. Acetone may form explosive mixtures in contact with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide and thioglycol.

**Hazardous decomposition product(s)**

Carbon monoxide, Carbon dioxide, Acrid smoke

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

**Information on toxicological effects**Acetone (CAS No. 67-64-1)**Acute toxicity**

Oral LD50 = 5800 mg/kg (rat)  
Dermal LD50 >15800 mg/kg (rabbit)  
Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.

**Irritation / Corrosivity**

Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

**Sensitisation**

It is not a skin sensitiser.

**Repeated dose toxicity**

Oral NOAEL = 500 mg/kg/day (rat) (90-days)  
Inhalation NOAEC  $\geq$  3.515 mg/L (rat), Vapour

**Carcinogenicity**

It is unlikely to present a carcinogenic hazard to man.

| NTP | IARC | ACGIH | OSHA | NIOSH |
|-----|------|-------|------|-------|
| No. | No.  | No.   | No.  | No.   |

**Mutagenicity**

Negative

**Toxicity for reproduction**

Negative

**Other information**

None known.

Xylenes (CAS No.1330-20-7)**Acute toxicity**

Oral LD50 = 3520 mg/kg (rat)  
Dermal LD50 >5000 mg/kg (rabbit)  
Inhalation LC50 = 27.6 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness. May cause respiratory irritation.

**Irritation / Corrosivity**

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

**Sensitisation**

It is not a skin sensitiser.

**Repeated dose toxicity**

Oral NOAEL = 900 mg/kg/day (rat) (90-days)  
Inhalation NOAEL  $\geq$  19,000 ppm (rat)

**Carcinogenicity**

It is unlikely to present a carcinogenic hazard to man.

| NTP | IARC | ACGIH | OSHA | NIOSH |
|-----|------|-------|------|-------|
| No. | No.  | No.   | No.  | No.   |

**Mutagenicity**

Negative

**Toxicity for reproduction**

Negative

**Other information**

Contains: residual Toluene (CAS No. 108-88-3)  $\sim \leq$  0.13%.  
Studies in animals have shown that repeated exposures to toluene produce adverse reproductive effects. However, in similar animal studies, mixed xylenes containing up to 2.4% residual toluene did not result in reproductive or developmental toxicity. As such, this product has not been classified as a reproductive toxicant.

# TIRE PREP

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

|                               |  |
|-------------------------------|--|
| <b>Acute toxicity</b>         | Oral: LD50 >5 g/kg-bw<br>Dermal: LD50 >2 g/kg-bw<br>Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat<br>May cause drowsiness or dizziness.<br>May be fatal if swallowed and enters airways. |
| <b>Irritation/Corrosivity</b> | Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.  |
| <b>Sensitization</b>          | It is not a skin sensitizer.   |
| <b>Repeated dose toxicity</b> | NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)<br>LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)<br>May cause drowsiness or dizziness.   |
| <b>Carcinogenicity</b>        | No data. It is unlikely to present a carcinogenic hazard to man.   |

| NTP | IARC | ACGIH | OSHA | NIOSH |
|-----|------|-------|------|-------|
| No. | No.  | No.   | No.  | No.   |

|                              |  |
|------------------------------|--|
| <b>Mutagenicity</b>          | There is no evidence of mutagenic potential. |
| <b>Reproductive toxicity</b> | Not available                                |

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

|            |   |
|------------|---|
| Short term | LL50 (96 hour): >13.4 mg/L ( <i>Oncorhynchus mykiss</i> )<br>EL50 (48 hour): 3 mg/l ( <i>Daphnia magna</i> , mobility)<br>EC50 (96 hour): 13 mg/l ( <i>Pseudokirchnerella subcapitata</i> ) |
|------------|---|

|           |   |
|-----------|---|
| Long Term | NOELR (28 days) 1.5 mg/l ( <i>Fish</i> ) QSAR<br>LOEC (21 days): 0.32 mg/l ( <i>Daphnia magna</i> )<br>NOEL (96 hour) 6.3 mg/l ( <i>Algae</i> ) |
|-----------|---|

Acetone (CAS No. 67-64-1):

|            |  |
|------------|--|
| Short term | LC50 (96 hour): 5,540 mg/l (Rainbow Trout ( <i>Oncorhynchus mykiss</i> ))<br>LC50 (96 hour): 8,300 mg/l (Bluegill Sunfish ( <i>Lepomis macrochirus</i> ))<br>LC50 (48 hour(s)): 12,600 – 12,700 mg/l ( <i>Daphnia magna</i> )<br>EC50 (14 d): 3,020 mg/l (Algae ( <i>Chlorella pyrenoidosa</i> ))<br>EC50 (15 min): 14,500 mg/l (Bacteria ( <i>Photobacterium phosphoreum</i> )) |
| Long Term  | Not available.   |

|   |  |
|---|--|
| <b>Persistence and degradability</b>      | Readily biodegradable.                             |
| <b>Bioaccumulative potential</b>          | The product has low potential for bioaccumulation. |
| <b>Mobility in soil</b>                   | The product has high mobility in soil.             |
| <b>Results of PBT and vPvB assessment</b> | Not classified as PBT or vPvB.                     |
| <b>Other adverse effects</b>              | None known.  |

## SECTION 13: DISPOSAL CONSIDERATIONS

|                                |  |
|--------------------------------|--|
| <b>Waste treatment methods</b> | Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice. |
|--------------------------------|--|

# TIRE PREP

## SECTION 14: TRANSPORT INFORMATION

|                                     | <u>U.S. DOT</u>     | <u>Sea transport<br/>(IMDG)</u> | <u>Air transport<br/>(ICAO/IATA)</u> |
|-------------------------------------|---------------------|---------------------------------|--------------------------------------|
| <b>UN number</b>                    | 1950                | 1950                            | 1950                                 |
| <b>Proper Shipping Name</b>         | Aerosols, flammable | Aerosols, flammable             | Aerosols, flammable                  |
| <b>Transport hazard class(es)</b>   | 2.1                 | 2.1                             | 2.1                                  |
| <b>Packing group</b>                | Not applicable      | Not applicable                  | Not applicable                       |
| <b>Environmental hazards</b>        | None assigned       | None assigned                   | None assigned                        |
| <b>Special precautions for user</b> | None assigned       | None assigned                   | None assigned                        |

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

## SECTION 15: REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**TSCA (Toxic Substance Control Act)** - Inventory Status: All components listed or polymer exempt.

**Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):**

| Chemical Name | CAS No.  | Typical %wt. | RQ (Pounds) |
|---------------|----------|--------------|-------------|
| Acetone       | 67-64-1  | 48           | 5000        |
| m-Xylene      | 108-38-3 | 46           | 1000        |
| o-Xylene      | 95-47-6  | 15           | 1000        |
| p-Xylene      | 106-42-3 | 20           | 100         |
| Ethylbenzene  | 100-41-4 | <19          | 1000        |
| Toluene       | 108-88-3 | 0.14         | 1000        |

**SARA 311/312 - Hazard Categories:** See SECTION 2: HAZARDS IDENTIFICATION

**SARA 313 - Toxic Chemicals (40 CFR 372):**

| Chemical Name | CAS No.  | Typical %wt. |
|---------------|----------|--------------|
| m-Xylene      | 108-38-3 | 46           |
| o-Xylene      | 95-47-6  | 15           |
| p-Xylene      | 106-42-3 | 20           |
| Ethylbenzene  | 100-41-4 | <19          |
| Toluene       | 108-88-3 | 0.14         |

**SARA 302 - Extremely Hazardous Substances(40 CFR 355):**

| Chemical Name | CAS No. | Typical %wt. | TPQ (pounds) |
|---------------|---------|--------------|--------------|
| None          | ----    | ----         | ----         |

**California Proposition 65 List:**

| Chemical Name | CAS No.  | Type of Toxicity      |
|---------------|----------|-----------------------|
| Acetaldehyde  | 75-07-0  | Cancer                |
| Benzene       | 71-43-2  | Cancer; Developmental |
| Cumene        | 98-82-8  | Cancer                |
| Ethylbenzene  | 100-41-4 | Cancer                |
| Toluene       | 108-88-3 | Developmental         |

# TIRE PREP

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 9.

**Date of preparation:** September 10, 2025

**Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:**

**Hazard Statement(s)**

- H222: Extremely flammable aerosol.
- H225: Highly flammable liquid and vapor.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H402: Harmful to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

**Training advice:** None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.